

## Q8 Formula Excel 5W-40

Synthetic ACEA A3/B4 passenger car engine oil

### Description

Q8 Formula Excel 5W-40 is a synthetic allround high SAPS engine oil for passenger cars and light duty commercial vehicles. This product guarantees advanced engine protection and facilitates easy starting at low temperatures. It is designed to counter sludge formation and minimizes oil consumption. It meets the requirements of ACEA A3/B4.

### Applications

Q8 Formula Excel 5W-40 is developed for passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or diesel engines and direct injection diesel engines. It is especially recommended for high performance, multi-valve engines with a catalyst. It meets the requirements of ACEA A3/B4.

### Benefits

- Outstanding oil film strength under all engine operating conditions.
- Outstanding engine protection after cold starting.
- Excellent protection against rust and corrosion.
- Outstanding friction reduction.

### Specifications, recommendations and approvals

ACEA	A3/B4	PSA	B71 2296
API	CF	Renault	RN 0700 *
API	SN	Renault	RN 0710 *
Ford	M2C917-A	VAG	<b>VW 502.00</b>
GM	LL-B-025	VAG	<b>VW 505.00</b>
Iveco	18-1811 S1	VAG	VW 505.01
MB	<b>229.3</b>	Volvo Cars	VCC 95200356

Color code blue = officially approved

\* Pending approval

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.853
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.3
Kinematic Viscosity, 40 °C (extrapolated)	D 445	mm <sup>2</sup> /s	89.2
Viscosity Index	D 2270	-	168
Apparent Viscosity, -30 °C	D 5293	mPa.s	6200
Flash Point, COC	D 92	°C	240
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Excel 5W-40 is **1.22** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

