

Q8 Formula Ultra V 0W-20

Synthetic Volvo VCC RBS0-2AE passenger car engine oil

Description

Q8 Formula Ultra V 0W-20 is a superior low SAPS passenger car engine oil for Volvo Euro 6 engines. This lubricant offers 3,4% fuel saving according to the M 111 fuel economy test, extends oil drain intervals and provides ultimate protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts provides best-in-class protection for aftertreatment systems.

Applications

Q8 Formula Ultra V 0W-20 is especially developed for Volvo Euro 6 passenger car engines requiring Volvo VCC RBS0-2AE and meets the latest ACEA C5 requirements.

Benefits

- Exceptional fuel economy improvement up to 3,4%.
- Outstanding engine protection after cold starting.
- Superb protection for exhaust catalyst and diesel particulate filter.
- Extended drain interval capability
- Outstanding oil film strength under all engine operating conditions.

Specifications, recommendations and approvals

ACEA	C6	Ford	M2C962-A1
API	SP	ILSAC	GF-6A
API	SP-RC	Jaguar Land Rover	STJLR.03.5006
API	SQ	MB	229.71
Chrysler	MS-12145	MB	229.72
Fiat	9.55535-GSX	Volvo Cars	VCC C6SP *
Ford	M2C947-B1	Volvo Cars	VCC RBS0-2AE
Ford	M2C954-A1		

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,845
Viscosity Grade	-	-	SAE 0W-20
Kinematic Viscosity, 40 °C	D 445	mm ² /s	48,7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9,2
Viscosity Index	D 2270	-	175
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>2,6
Apparent Viscosity, -35 °C	D 5293	mPa.s	5700
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	204

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Ultra V 0W-20 is **1.36 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

