PRODUCT DATA SHEET

Q8 Allroads 4T 10W-40

Excellent synthetic motorcycle oil

Description

Q8 Allroads 4T 10W-40 is an excellent synthetic motorcycle oil that matches various driving conditions. Its robust formulation provides a strong film on all moving parts to guarantee an outstanding wear protection and gear pitting in all driving conditions. Q8 Allroads 4T 10W-40 exceeds the top international OEM requirements.

Applications

Q8 Allroads 4T 10W-40 is used in on-road motorcycles (daily transportation) and off-road motorcycles with dry or wet clutch. It is used in both air and water cooled engines.

Benefits

- *Excellent engine performance at extreme driving conditions.*
- *Outstanding year round properties.*
- *Excellent protection against rust and corrosion.*
- *Outstanding bearing lubrication and cylinder wear protection.*
- *Excellent cleanliness and wear protection for all components.*

Specifications, recommendations and approvals

API	SL	**JASO**	MA2

Properties

	Method	Unit	Typical
Density, 20 ˚C	*D 4052*	*g/ml*	*0,861*
Density, 15 ˚C	*D 4052*	*g/ml*	*0,864*
Viscosity Grade	*-*	*-*	*10W-40*
Kinematic Viscosity, 40 ˚C	*D 445*	*mm²/s*	*98*
Kinematic Viscosity, 100 ˚C	*D 445*	*mm²/s*	*14.3*
Viscosity Index	*D 2270*	*-*	*150*
Pour Point	*D 97*	*˚C*	*-39*
Flash Point, COC	*D 92*	*˚C*	*231*

The figures above are not a specification. They are typical figures obtained within production tolerances.