

Q8 Allroads 4T 15W-50

Advanced synthetic motorcycle oil

Description

Q8 Allroads 4T 15W-50 is an advanced synthetic motorcycle oil that matches various driving conditions. Its robust formulation provides a strong film on all moving parts to guarantee an optimum engine wear protection and gear pitting in all driving conditions. Q8 Allroads 4T 15W-50 exceeds the top international OEM requirements.

Applications

Q8 Allroads 4T 15W-50 is used in on-road motorcycles (daily transportation) and off-road motorcycles with dry or wet clutch. It is used in both air and water cooled engines.

Benefits

- Outstanding friction reduction allowing high load capacity.
- Excellent protection against rust and corrosion.
- Outstanding bearing lubrication and cylinder wear protection.

Specifications, recommendations and approvals

API

SL

JASO

MA2

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,871
Viscosity Grade	-	-	15W-50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	145,6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	18,7
Viscosity Index	D 2270	-	145
Flash Point, COC	D 92	°C	236
Pour Point	D 97	°C	-36

The figures above are not a specification. They are typical figures obtained within production tolerances.