

## Q8 Antifreeze Long Life OAT Premixed

Superior premixed long life antifreeze

### Description

Q8 Antifreeze Long Life OAT Premixed is a superior fluid that protects against freezing, boiling and corrosion of the cooling system. The antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Q8 Antifreeze Long Life OAT Premixed is obtained by non-depleting corrosion inhibitors.

### Applications

Q8 Antifreeze Long Life OAT Premixed is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

### Benefits

- Best-in-class cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.
- Exceptional long life protection against all forms of corrosion.
- Superior and extended corrosion protection due to synergistic effects.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime

### Specifications, recommendations and approvals

<b>AGCO</b>		<b>Iveco</b>	18-1830
<b>Cummins</b>	CES 14439	<b>Leyland Trucks</b>	DW03245403
<b>Cummins</b>	CES 14603	<b>MAN</b>	324 Type SNF
<b>DAF</b>	74002	<b>MAN</b>	325 Type SNF
<b>Daimler Truck AG</b>	DTFR 29C110 (MB 325.3)	<b>Renault</b>	41-01-001/- -S Type D
<b>Daimler Truck AG</b>	DTFR 29D110 (MB 326.3)	<b>Renault</b>	41-01-001/- -T
<b>Detroit Diesel</b>	93K217	<b>Rolls-Royce Bergen</b>	2.13.01
<b>Detroit Diesel</b>	DFS 93K227	<b>Stellantis</b>	FPW 9.55523
<b>Deutz</b>	DQC CB-14	<b>Stellantis</b>	GMW 18270
<b>Ford</b>	M97B44-D	<b>Stellantis</b>	GMW 3420
<b>Foton</b>	Q-FPT 2313005-2013	<b>Tedom</b>	
<b>GM</b>	B 040 1065	<b>VAG</b>	VW TL 774 D (G12)
<b>GM</b>	GMW 18270	<b>VAG</b>	VW TL 774 F (G12+)
<b>GM</b>	GMW 3420	<b>Wärtsilä</b>	
<b>Isuzu</b>			

### Properties

	Method	Unit	Typical
Density, 20 °C	D 1122	kg/l	1.072
Colour	Visual	-	orange/red
Freezing Protection	D 1177	°C	-37
Equilibrium Reflux Boiling Point	D 1120	°C	109
pH	D 1287	-	8.7

The figures above are not a specification. They are typical figures obtained within production tolerances.