

Q8 Dino 3.5

Asphalt release agent

Description

Q8 Dino 3.5 is a superior versatile asphalt release agent designed to be used as anti-sticking agent for cleaning tools and machinery. The product has a very low odour, low misting properties and is solvent free. Q8 Dino 3.5 has a low viscosity that leads to easy application. It has a high flash point and can be used in high temperatures environments.

Applications

Q8 Dino 3.5 is used as an anti-sticking oil for asphalt plants, asphalt trucks and for cleaning tools at the work site. It is also applied as a cleaning solution in workshop floors.

The intent of asphalt release agents is to eliminate harmful stripping products that have been in contact with bituminous products and to strip the asphalt from aggregates that cause detrimental pavement failures.

Benefits

- User-friendly and smooth operation
- Odorless
- Easy application by spraying
- Prevents sticking
- High flash point
- Effortless and safe application for operators
- Free of solvents
- Readily biodegradable

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0,813
Kinematic Viscosity, 40 °C	D 445	mm ² /s	3.5
Pour Point	D 97	°C	-15
Flash Point, COC	D 92	°C	135
Colour	D 1500	-	L 0.5
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Biodegradability, 28 days	OECD 301 B	%	61

The figures above are not a specification. They are typical figures obtained within production tolerances.