

## Q8 LHM+

Green hydraulic fluid with ultra-high viscosity index (> 300)

### Description

Q8 LHM+ is a hydraulic fluid with an ultra high viscosity index (>300) that meets the Citroën & Peugeot requirements PSA B71 2710. It is water-resistant and is designed to provide advanced performance in humid conditions.

### Applications

Q8 LHM+ is used for hydraulic systems in Citroën cars with hydraulic suspension and brake/clutch systems, for models XM, BX, CX, GS / GSA, Acadiane, C35, Ami Super, SM, M35, 2CV, Dyane, Méhari, Ami 8 (front disc brakes), ID / DS (models >09/1966). Suited for Rolls-Royce, Bentley, Maserati and Peugeot passenger cars and for Fiat / Iveco trucks requiring one of the listed specifications.

### Benefits

- Excellent low temperature viscosity performance for preserved suspension comfort and performance during cold driving conditions.
- Outstanding system metal corrosion protection.
- Outstanding stable fluid characteristics.
- Outstanding compatibility with system rubber seals

### Specifications, recommendations and approvals

ISO 7308      PSA B71 2710

### Properties

|                             | Method   | Unit  | Typical  |
|-----------------------------|----------|-------|----------|
| Density, 15 °C              | D 4052   | g/ml  | 0,84     |
| Kinematic Viscosity, 40 °C  | D 445    | mm²/s | 18       |
| Kinematic Viscosity, 100 °C | D 445    | mm²/s | 6        |
| Viscosity Index             | D 2270   | -     | 340      |
| Kinematic Viscosity, -40 °C | D 445    | mm²/s | 1200 max |
| Equilibrium boiling point   | ISO 3405 | °C    | 240 min. |
| Pour Point                  | D 97     | °C    | -62      |
| Flash Point, COC            | D 92     | °C    | 121      |

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 LHM+ is **2.11 kg CO<sub>2</sub>eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

