

Q8 Mahler G10 SAE 40

High performance stationary gas engine oil

Description

Q8 Mahler G10 is a high performance gas engine oil, based on premium Group II (hydrotreated) base fluid. This product is designed as part of the Q8Oils clean technology program, which benefits from in-house developments and customized solutions.

Q8 Mahler G series products meet the challenges of the latest generation (steel piston, high output and low emission) engines, ensuring clean engines in combination with extended drain performance.

Applications

Engine

Lean-burn and stoichiometric four-stroke stationary gas engines, including high BMEP type.

Operations

Mild to severe conditions, including high pressure, high load and high temperature operations.

Gas type

Wide variety of gases, including natural gas, biogas, landfill gas, sewage gas, mine gas and wood gas. Exceptional performance in applications using gas with high H₂S content.

Features

Benefits

Own product development

In-house developed outstanding additive package in combination with a carefully chosen Group II base oil

Extended drain

Excellent balanced gas engine oil, providing outstanding engine cleanliness, low oil consumption with outstanding protection for the cylinder head valves and valve seats, significantly reducing the total operational costs

Engine performance

Outstanding resistance against pre-ignition and knocking ensuring high engine efficiency

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,892
Viscosity Grade	-	-	SAE 40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	119.8
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.3
Viscosity Index	D 2270	-	106
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	250
Sulfated Ash	D 874	% mass	1.0
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

The original manufacturers recommendation should be followed.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mahler G10 SAE 40 is **1.31** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

