

## Q8 Rembrandt EP 00

Advanced lithium extreme pressure grease

### Description

Q8 Rembrandt EP 00 is a multi-purpose lithium grease with extreme pressure properties that is designed for centralised lubrication systems. The grease has advanced anti-wear properties and excellent rust-protection when used in the presence of water. Q8 Rembrandt EP 00 is temperature resistant up to 110°C and has a smooth structure that leads to an optimum pumpability and roll stability.

### Applications

Q8 Rembrandt EP 00 is applied in industrial and automotive applications. The grease is used for chassis lubrication with a centralised system (such as trucks and off-highway equipment).

Q8 Rembrandt EP 00 is also suited as a lubricant for other industrial applications that are not able to retain gear oils due to poorly closed gear cases.

### Benefits

- Lower downtime and an improved maintenance efficiency
- Advanced anti-wear characteristics
- Optimum roll stability
- Advanced flow properties of the grease

### Specifications & Approvals

DIN 51502 KP00K-30 ISO 6743 L-XCCHB00

### Properties

	Method	Unit	Typical
Soap type	-	-	Lithium
Colour	Visual	-	Brown
Consistency, NLGI No.	NLGI	-	NLGI 00
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	415
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	280
Dropping Point	D 566	°C	170
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Four Ball Test, Weld Load	IP 239	N	2450

The figures above are not a specification. They are typical figures obtained within production tolerances.