

Q8 Stravinsky N 68

High performance refrigeration compressor oil

Description

Q8 Stravinsky N 68 is a high performance refrigeration compressor oil. It is developed with premium selected naphtenic base fluid. The product is recommended for use with CFC-, HCFC- or traditional type refrigerant (such as ammonia). The low pour point and outstanding fluidity at low temperature ensure problem-free operations.

Applications

Reciprocating- and rotary refrigerator compressors
Industrial applications such as refrigerators and freezers
Refrigerating systems handling CFC-, HCFC- or traditional type refrigerant (such as ammonia)

Features

Benefits

Enhanced technology	Fully compatible with mineral oils and normally used elastomer/plastic materials in compressor equipment
Extended drain	Advanced oxidative stability, guaranteeing long oil life under continuous and severe operating conditions
Safety	Tailored to the specific needs of your equipment to ensure safe and reliable operations

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,906
Kinematic Viscosity, 40 °C	D 445	mm ² /s	68
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.9
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	220
Colour	D 1500	-	1.0
Aniline Point	D 611	°C	78

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky N, it is recommended to flush the compressor lubricant system.