

Q8 da Vinci AM 4

Very light demoulding oil with exceptional anti-mist properties

Description

Q8 da Vinci AM 4 is a superior solvent free demoulding oil with anti-rust inhibitors and anti-mist additives to prevent inhalation of vapours. The reactive layer in this easily applicable oil creates a layer between concrete and mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci AM 4 provides an exceptional smooth concrete surface finish and a clean mould.

Applications

Q8 da Vinci AM 4 is used for demoulding of prefab concrete foundation piles and on-site elements such as floors, stairs and balconies. It is applied in steel and plywood moulds.

Q8 da Vinci AM 4 is also used as an anti-sticking oil for asphalt plants, asphalt trucks and for cleaning tools at the work site.

Benefits

- Extremely effective demoulding operation
- Durable & reliable end product quality
- Outstanding smooth surface
- Enriched with special additives
- Light colour
- Outstanding anti-rust properties
- Easy to use
- Prevents sticking

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0,813
Kinematic Viscosity, 40 °C	D 445	mm ² /s	4.0
Pour Point	D 97	°C	-24
Flash Point, COC	D 92	°C	128
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 da Vinci AM 4 is **1.26** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

