

## Q8 van Gogh EP 150

High performance turbine oil

### Description

Q8 van Gogh EP 150 is a high performance turbine oil based on selected premium base fluids. This product is developed for use in steam and gas turbines as well as combined cycle applications, including geared turbines. Q8 van Gogh EP 150 meet the challenges of the latest generation turbines making it suitable to operate under mild to severe conditions. Designed as part of the Q8Oils clean technology program to ensure superior varnish/deposit control and good load carrying capabilities in combination with long oil life.

### Applications

Industrial steam- and gas turbines, including geared turbines and combined cycle operations  
Hydroelectric turbines  
Circulation systems where turbine oil quality is required  
Centrifugal- and axial pumps, and turbo-compressors, where turbine oil quality is recommended

### Features

### Benefits

<b>Turbine performance</b>	Long trouble free service life, excellent turbine protection and outstanding resistance against ageing
<b>Enhanced technology</b>	Developed with outstanding anti-wear/extreme pressure protection to meet the load carrying requirements of geared turbines
<b>Lower operational costs</b>	Specifically developed with excellent protection against the formation of varnish

### Specifications & Approvals

<b>ASTM</b>	D 4304, Type II (EP)	<b>ISO</b>	6743-5 L-TSE
<b>ISO</b>	6743-5 L-TGE		

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,887
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	150
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.7
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.13
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	262
Colour	D 1500	-	L 2.0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
FZG Test, A/8.3/90	DIN 51354	load stage	10

The figures above are not a specification. They are typical figures obtained within production tolerances.