

Q8 Trans XGS 75W-90

Full synthetic total driveline SAE J2360 transmission fluid

Description

Q8 Trans XGS 75W-90 is a superior full synthetic transmission fluid designed for heavy duty driveline components requiring special low temperature fluidity. The product offers best-in-class protection against extreme pressure and wear due to exceptional stability in high as well as low temperatures. This results in optimized lubrication of hypoid and non-hypoid axles.

Applications

Q8 Trans XGS 75W-90 is designed for heavy duty components in mining or construction vehicles such as rear-axles, final drives and selected manual transmissions, requiring low temperature fluidity. It meets the latest requirements of all major OEMs such as SAE J 2360, Scania STO 2:0A FS, Volvo 97312 and MAN 342 type S1.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Superior axle wear protection.
- Exceptional wear protection under heavy duty operating conditions.
- Superior protection against rust and corrosion.

Specifications / Recommendations / Approvals

API	GL-4	Mack	GO-J
API	GL-5	Meritor	GO MTR 076S
API	MT-1	SAE	J 2360
Case New Holland	MAT 3516-C	Scania	STO 1:0
Daimler Truck AG	DTFR 12B100 (MB 235.0)	Scania	STO 1:1 G *
Daimler Truck AG	DTFR 12B140 (MB 235.8) *	Scania	STO 2:0 A
Detroit Diesel	DFS 93K219.01	Scania	STO 2:0 A FS
Ferrari	GL-4	Scania	STO 2:0 G
Ferrari	GL-5	VAG	VW G 052 911
Iveco	18-1805 RAS1	Volvo	97312
MAN	341 Type E3	ZF	TE-ML 02B
MAN	341 Type GA1	ZF	TE-ML 05A
MAN	341 Type Z2	ZF	TE-ML 12L
MAN	342 Type M2	ZF	TE-ML 12N
MAN	342 Type M3	ZF	TE-ML 16F
MAN	342 Type S1	ZF	TE-ML 17B
MB	235.8 (DTFR 12B140)	ZF	TE-ML 19C
MIL	L-2105D	ZF	TE-ML 21A
MIL	PRF-2105E	ZF	TE-ML 24A

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,869
Density, 20 °C	D 4052	g/ml	0,861
Viscosity Grade	SAE J306	SAE	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm ² /s	108
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15.6
Viscosity Index	D 2270	-	153
Brookfield Viscosity, -40 °C	D 2983	Pa.s	70
Pour Point	D 97	°C	-51
Flash Point, COC	D 92	°C	180

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Trans XGS 75W-90 is **2.13 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

