PRODUCT DATA SHEET

Q8 Axle Oil GL-5 75W-90

Synthetic based API GL-5 transmission fluid

Description

Q8 Axle Oil GL-5 75W-90 is a premium performance transmission fluid, developed for heavy duty vehicles and passenger cars. It can be used for final drives, differentials, rear axles and transfer boxes meeting the API GL-5 specification.

Applications

Q8 Axle Oil GL-5 75W-90 is developed for heavy duty vehicles and passenger cars. It can be used for final drives, differentials, rear axles and transfer boxes, meeting the API GL-5 specification.

Benefits

- *Outstanding axle wear protection.*
- *Superb gear protection under heavy duty conditions.*
- *Outstanding protection against rust and corrosion.*
- *Improved shear stability for a stable viscosity during use*

Specifications, recommendations and approvals

API	GL-5	**ZF**	TE-ML 16B
MIL	L-2105D	**ZF**	TE-ML 17B
ZF	TE-ML 05A	**ZF**	TE-ML 19B

Properties

	Method	Unit	Typical
Density, 15 °C	*D 4052*	*g/ml*	*0,87*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*101.1*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*14.8*
Viscosity Index	*D 2270*	*-*	*152*
Brookfield Viscosity, -40 °C	*D 2983*	*Pa.s*	*108.1*
Flash Point, COC	*D 92*	*°C*	*168*

The figures above are not a specification. They are typical figures obtained within production tolerances.