PRODUCT DATA SHEET

Q8 Axle Oil TP 80W-90

Axle Fluid LS

Description

Q8 Axle Oil TP 80W-90 is a universal API GL-5 fluid for heavy duty equipment having limited slip differentials and wet brakes, offering supreme wear protection and excellent dynamic braking performance for smooth and safe brake operation. This product provides significant reduction in brake chatter improving mechanical transmission component life and extreme pressure protection.

Applications

Q8 Axle Oil TP 80W-90 is specifically designed for agricultural and off-highway/construction equipment requiring API GL-5 performance in combination with limited slip differentials and wet brakes.

Benefits

- *Outstanding protection against wear and extends component life.*
- *Excellent extreme pressure protection*
- *Extends equipment life*
- *Superb gear protection under heavy duty conditions.*
- *Outstanding protection against rust and corrosion.*

Specifications, recommendations and approvals

API	GL-5 LS	**John Deere**	JDQ-96
John Deere	JDM J20C		

Properties

	Method	Unit	Typical
Density, 15 °C	*D 4052*	*g/ml*	*0,9*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*147*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*15.5*
Viscosity Index	*D 2270*	*-*	*106*
Brookfield Viscosity, -26 °C	*D 2983*	*mPa.s*	*150*
Pour Point	*D 97*	*°C*	*-21*
Flash Point, COC	*D 92*	*°C*	*182*

The figures above are not a specification. They are typical figures obtained within production tolerances.