

## Q8 Chain Oil BIO

Biodegradable chain and chainsaw fluid

### Description

Q8 Chain oil Bio is readily biodegradable chain and chainsaw fluid. Its bio-based components are carefully selected for usage in environmentally sensitive areas. Q8 Chain oil Bio is suitable for a wide range of temperatures and has outstanding wear-, corrosion- and rust protection characteristics. Its low oil consumption is a result of the strong adhesive oil film.

### Applications

Q8 Chain Oil Bio is perfect for environmentally delicate areas and is used in agriculture, forestry, water works and marine. It is applied in chains, slides of chainsaws and also in slideway and guides in industrial applications.

### Benefits

- Harmless to the environment
- Free of hazardous components
- Readily biodegradable
- User-friendly and smooth operation
- High adherent characteristics
- Advanced performance against wear

### Specifications & Approvals

ISO 6743-1 L-AC

### Properties

|                            | Method     | Unit               | Typical |
|----------------------------|------------|--------------------|---------|
| Kinematic Viscosity, 40 °C | D 445      | mm <sup>2</sup> /s | 56      |
| Density, 15 °C             | D 4052     | g/ml               | 0,918   |
| Pour Point                 | D 97       | °C                 | -30     |
| Flash Point, COC           | D 92       | °C                 | 280     |
| Biodegradability, 28 days  | OECD 301 B | %                  | >80     |

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Q8 Chain Oil Bio should not be used for lubricating the engine of the chain saw.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Chain Oil BIO is **1.26** kg CO<sub>2</sub>-eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF



[www.Q8Oils.com](http://www.Q8Oils.com)