PRODUCT DATA SHEET

Q8 T 40 75W-90

Synthetic API GL-4 transmission fluid

Description

Q8 T 40 75W-90 is an outstanding synthetic manual transmission fluid for 4 or 5 speed passenger cars and vans. This product delivers easy gear shifting, even at low temperatures. It provides superb protection against wear, corrosion and rust.

Applications

Q8 T 40 75W-90 is developed for passenger cars and vans that require the API GL-4 specification.

Benefits

- *Outstanding protection against wear and extends component life.*
- *Excellent easy gear shifting at low temperatures.*
- *Outstanding protection against rust and corrosion.*
- *Reduces drive-line operating temperatures.*

Specifications, recommendations and approvals

API	GL-4	**Ford**	M2C200-C
Fiat	9.55550-MX3	**Ford**	SQM-2C9008-A
Fiat	9.55550-MZ1	**Mazda**	
Fiat	9.55550-MZ11	**Mitsubishi**	
Fiat	9.55550-MZ3	**ZF**	Synchromesh transmissions
Fiat	9.55550-MZ4		

Properties

	Method	Unit	Typical
Density, 15 ˚C	*D 4052*	*g/ml*	*0,85*
Viscosity Grade	*-*	*-*	*SAE 75W-90*
Kinematic Viscosity, 40 ˚C	*D 445*	*mm²/s*	*89.4*
Kinematic Viscosity, 100 ˚C	*D 445*	*mm²/s*	*14.3*
Viscosity Index	*D 2270*	*-*	*166*
Brookfield Viscosity, -40 ˚C	*D 2983*	*Pa.s*	*64,2*
Pour Point	*D 97*	*˚C*	*-42*
Flash Point, P-M	*D 93*	*˚C*	*202*

The figures above are not a specification. They are typical figures obtained within production tolerances.