PRODUCT DATA SHEET

Q8 Terra 4000 UTTO CVT 75W-85

Exceptional Synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 Terra 4000 UTTO CVT 75W-85 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T Q8 Terra 4000 UTTO CVT 75W-85 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 Terra 4000 UTTO CVT 75W-85 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

Benefits

- *Superior viscosity retention providing smoothless CVT operation.*
- *Best-in-class oxidation stability.*
- *Superior frictional properties for smooth brake operation.*
- *Superior response of hydraulic components.*
- *Maximum compatibility with conventional elastomers.*

Specifications, recommendations and approvals

AGCO	CVT ML 200	**Massey Ferguson**	CMS M 1141 / M 1143 / M 1145
API	GL-4	**New Holland**	NH 410-B / NH 410-C
Case	MS 1206	**Same Deutz Fahr**	UTTO
Case	MS 1207	**Valtra**	G2-08 (XT-60)
Case	MS 1209	**Valtra**	G2-B10 (XT-60+)
Case	MS 1210	**ZF**	TE-ML 03E / 03G / 03L
Case New Holland	MAT 3505	**ZF**	TE-ML 05F
Case New Holland	MAT 3525	**ZF**	TE-ML 06B
Case New Holland	MAT 3540	**ZF**	TE-ML 06D
Case New Holland	MAT 3541	**ZF**	TE-ML 06E
Case New Holland	MAT 3544	**ZF**	TE-ML 06F
Case New Holland	MAT 3552-A	**ZF**	TE-ML 06K
Case New Holland	MAT 3553-A	**ZF**	TE-ML 06L
Caterpillar	SATO	**ZF**	TE-ML 06M
Claas	CVT	**ZF**	TE-ML 06N
Deutz	Allis AC Power Fluid 821 XL	**ZF**	TE-ML 06P
Fendt	FWN 81001	**ZF**	TE-ML 06R
Fendt	Vario	**ZF**	TE-ML 06S
John Deere	JDM J20C	**ZF**	TE-ML 06T
Komatsu	KES 07.866	**ZF**	TE-ML 17E
Kubota	UDT / Super UDT / UDT-HD	**ZF**	TE-ML 21F
Massey Ferguson	CMS M 1135		

Properties

	Method	*Unit*	*Typical*
Viscosity Grade	*SAE J300*	*SAE*	*10W-30*
Viscosity Grade	*SAE J306*	*SAE*	*75W-85*
Density, 15 °C	*D 4052*	*g/ml*	*0,861*
Density, 20 °C	*D 4052*	*g/ml*	*0,858*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*71.1*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*12.0*
Viscosity Index	*D 2270*	*-*	*166*
Brookfield Viscosity, -20 °C	*D 2983*	*mPa.s*	*3400*
Pour Point	*D 97*	*°C*	*-42*
Flash Point, COC	*D 92*	*°C*	*240*

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT 75W-85 is **1.30** kg CO_2eq / kg.*
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.
For more info check here

we take care

PRODUCT CARBON FOOTPRINT METHOD VALIDATED BY:
PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF
VINÇOTTE