PRODUCT DATA SHEET

Q8 Terra 4000 UTTO CVT LV 75W-80

Exceptional synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 Terra 4000 UTTO CVT LV 75W-80 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 Q8 Terra 4000 UTTO CVT LV 75W-80 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 Terra 4000 UTTO CVT LV 75W-80 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

Specifications, recommendations and approvals

AGCO	CVT ML 200	**Massey Ferguson**	CMS M 1135
API	GL-4	**Massey Ferguson**	CMS M 1141 / M 1143 / M 1145
Case	MS 1206	**New Holland**	NH 410-B / NH 410-C
Case	MS 1207	**Same Deutz Fahr**	UTTO
Case	MS 1209	**Valtra**	G2-08 (XT-60)
Case	MS 1210	**Valtra**	G2-B10 (XT-60+)
Case New Holland	MAT 3505	**ZF**	TE-ML 03E / 03G / 03L
Case New Holland	MAT 3525	**ZF**	TE-ML 05F
Case New Holland	MAT 3540	**ZF**	TE-ML 06B
Case New Holland	MAT 3541	**ZF**	TE-ML 06D
Case New Holland	MAT 3544	**ZF**	TE-ML 06E
Case New Holland	MAT 3552-A	**ZF**	TE-ML 06F
Case New Holland	MAT 3553-A	**ZF**	TE-ML 06K
Caterpillar	SATO	**ZF**	TE-ML 06L
Claas	CVT	**ZF**	TE-ML 06N
Deutz	Allis AC Power Fluid 821 XL	**ZF**	TE-ML 06P
Fendt	FWN 81001	**ZF**	TE-ML 06R
Fendt	Vario	**ZF**	TE-ML 06S
John Deere	JDM J20C	**ZF**	TE-ML 06T
Komatsu	KES 07.866	**ZF**	TE-ML 17E
Kubota	UDT / Super UDT / UDT-HD	**ZF**	TE-ML 21F

Properties

	Method	Unit	Typical
Viscosity Grade	*SAE J300*	*SAE*	*10W-30*
Viscosity Grade	*SAE J306*	*SAE*	*75W-80*
Density, 15 °C	*D 4052*	*g/ml*	*0.865*
Density, 20 °C	*D 1122*	*kg/l*	*0,862*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*9.8*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*60,2*
Viscosity Index	*D 2270*	*-*	*148*
Brookfield Viscosity, -20 °C	*D 2983*	*mPa.s*	*2500*
Pour Point	*D 97*	*°C*	*-42*
Flash Point, COC	*D 92*	*°C*	*246*

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT LV 75W-80 is **1.30** kg CO_2eq / kg.*
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.
For more info check here

we take care

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

VINÇOTTE